

## Forbo FloorCare method

### Coral brush blend, brush pure, classic, duo, T32 marine, welcome, logo

Coral entrance mats will, by their nature and location, be one of the most 'abused' of all floor coverings within a building. Thorough and regular cleaning is essential to ensure optimum performance and to extend the lifespan of the products. The optimal frequency of cleaning is determined by the traffic volume and the level of soiling.

#### Daily cleaning



It is essential to remove dry soiling at least once a day. The most effective method is to use vacuum cleaners that incorporate a mechanically driven rotating brush or suction-only machines with a rotating brush attachment. Vacuum slowly and in all directions across the matting, to get the full effect of the combined suction and brushing.

#### Regular cleaning



##### Spot cleaning

Gently clear away the spillage from the surface with a blunt scraper. Treat what is left of the spillage with a proprietary carpet spot cleaner (for polyamide pile floor coverings) and rinse with clean water. Allow to dry. High traffic areas need additional attention, to remove concentrated surface soiling and reduce the appearance of "traffic lanes".

- Dry extraction: this method uses a moist compound that is impregnated with water, detergent and safe-to-use solvents.
- Cylindrical brush extraction: this method uses machines with counter-rotating brushes, but this time a proprietary carpet cleaning solution is brushed into the pile and the dirty water returned straight to the machine. Ensure all detergent residues are removed by rinsing thoroughly with clean water.

#### Scheduled maintenance



- At intervals, the matting should be treated with a deeper cleaning process called "spray extraction". This removes soiling from the base of the pile and restores the surface texture to optimise its "clean-off" performance. Factors like the type and amount of traffic, as well as the effectiveness of "Daily cleaning" and "Regular cleaning" will govern how often this deep cleaning is needed.
- This process can be carried out using either a spray extraction machine or a 3-in-1 spray and brush machine. When wet cleaning is not possible a powder cleaning is the best solution. Ensure all detergent residues are thoroughly rinsed with clean water.

**Note:** Use hot water extraction machine at a temperature not exceeding 50°C

**Note:** Removal of chewing gum is best achieved by the use of gum removal gels.

[www.forbo-flooring.co.uk/efs](http://www.forbo-flooring.co.uk/efs) Samples tel: 0800 731 2369